



### MATERIALS OPTIONS

- FACES: CARBON / STAINLESS / SILICON & TUNGSTEN CARBIDE
- ELASTOMERS: BUNA / VITON / EPDM / AFLAS
- METAL: 304SS / 316SS

### OPERATING CONDITIONS

- TEMPERATURE: -40 TO 400F (-40 TO 204 C)
- PRESSURE RANGE: UP TO 150 PSI (10.7 BAR)

### PRODUCT DESCRIPTION

- EQUIVALENT: JOHN CRANE - TYPE 2
- ROTACION: BIDIRECIONAL
- FACES: BELLOVED TO COMPENSATE FOR WEAR
- OPERATING LENGTH: EQUAL TO C31 (L1 DIMENSION)
- APPLICATION: INDUSTRIAL
- DRIVE: BAND & NOTCHES FOR RUGGED APPLICATIONS

## DIMENSIONAL INFORMATION

D (in)	D1	L1	D2	L2
1/2	1.187	0.813	1.000	0.312
5/8	1.312	0.875	1.250	0.405
3/4	1.437	0.875	1.375	0.405
7/8	1.562	0.937	1.500	0.405
1	1.791	1.000	1.625	0.437
1 1/8	1.909	1.062	1.750	0.437
1 1/4	2.062	1.062	1.875	0.437
1 3/8	2.205	1.125	2.000	0.437
1 1/2	2.331	1.125	2.125	0.437
1 5/8	2.638	1.375	2.375	0.500
1 3/4	2.750	1.375	2.500	0.500
1 7/8	2.875	1.500	2.625	0.500
2	3.000	1.500	2.750	0.500
2 1/8	3.250	1.687	3.000	0.562
2 1/4	3.375	1.687	3.125	0.562
2 3/8	3.500	1.812	3.250	0.562
2 1/2	3.625	1.812	3.375	0.562
2 5/8	3.875	1.937	3.375	0.626
2 3/4	4.000	1.937	3.500	0.626
2 7/8	4.125	2.062	3.750	0.626
3	4.250	2.062	3.875	0.626

■ Rotary Dimensions  
■ Stationary Dimensions (Cup)

### STATIONARY SEATS (IN)

