



## FIBRA SINTETICA

### STYLE 1162IB



Syntex fiber thoroughly impregnated with PTFE, a break-in lubricant is added for start-up. An economical PTFE general service packing. Interlock braid.

**Temperature:** To 500°F (260°C)  
**pH:** 2-10  
**Speed:** 2000 FPM  
**Pressure:** To 300 PSI (20 bar)  
**Construction:** Interlock Braid

SIZE	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"
ft / lb	80,0	50,0	26,0	19,0	13,0	10,0	7,4	5,0	4,5	3,2	2,5	1,9
m / lb	24,4	15,2	7,9	5,8	4,0	3,0	2,3	1,5	1,4	1,0	0,8	0,6

### STYLE 1398



Syntex fiber packing thoroughly impregnated with a high temperature lubricant. Finished packing is surface graphited. An asbestos replacement packing for general service use on pumps and valves.

**Temperature:** To 500°F (265°C)  
**pH:** 4-10  
**Speed:** 1500 FPM  
**Pressure:** To 300 PSI (20 bar)  
**Construction:** Interlock Braid

SIZE	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"
ft / lb	128,0	56,0	31,0	21,0	16,0	11,0	8,6	6,7	5,8	4,0	3,0	2,1
m / lb	39,0	17,1	9,5	6,4	4,9	3,4	2,6	2,0	1,8	1,2	0,9	0,6

### STYLE 1152



Special syntex fiber, with each strand impregnated with PTFE dispersion both prior to and after braiding. Finished packing also has a break-in lubricant. An asbestos replacement packing for general service applications. Good chemical resistance.

**Temperature:** To 500°F (260°C)  
**pH:** 0-12  
**Speed:** 2200 FPM  
**Pressure:** To 500 PSI (35 bar)  
**Construction:** Interlock Braid

SIZE	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"
ft / lb	88,0	48,0	25,0	16,6	12,0	8,5	6,4	5,7	4,2	2,9	2,6	1,7
m / lb	26,8	14,6	7,6	5,1	3,7	2,6	2,0	1,7	1,3	0,9	0,8	0,5



Sede principal

CRA 53 No. 14- 24 PUENTE ARANDA – Bogota Tel: (1) 262 8433 – 262 8453 – 413 6713 Cel: 310233374 – 312 4844802 servicioalcliente@ijmsas.com